



Notes- Unless otherwise specified:

Standard and Custom colors are available

- Fastening methods are:
1. Applied with 3M VHB 4910 Double Sided Clear Acrylic Tape (provided installed on Snowguard)
 2. Field applied RTV Silicone Adhesive Sealant
 3. Mechanical Fastening with Self Tapping Sheetmetal Screws using (4) provided holes.

Hold strength is dependent on fastening method.

Layout guidelines are as follows: 0-2/12 slope Horizontally stagger one row 2 feet on center pan to pan for every 20 feet of roof length.

3/12-6/12 slope Horizontally stagger two rows 2 feet on center pan to pan for every 20 feet of roof length.

6/12 and up slope Horizontally stagger three rows 2 feet on center pan to pan for every 20 feet of roof length.

Exact layout to be determined by designer/ architect with consideration for building codes, snow loads, roof design and other environmental considerations.

| | | | | | | | | | | | |
|---|--|--|--|---------|--|-----------------------------------|--|----------------------|--|---------------|--|
| UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: LINEAR: ANGULAR: | | | | FINISH: | | DEBUR AND BREAK SHARP EDGES | | DO NOT SCALE DRAWING | | REVISION A | |
| | | | | | | | | Sno-Safe LLC | | | |
| | | | | | | | | TITLE: Snow Guard | | | |
| | | | | | | | | DWG NO. Snosafe-001 | | A3 | |
| | | | | | | | | SCALE:1:1 | | SHEET 1 OF 1 | |
| DRAWN | | | | NAME | | SIGNATURE | | DATE | | | |
| CHK'D | | | | | | | | | | | |
| APPV'D | | | | | | | | | | | |
| MFG | | | | | | | | | | | |
| Q.A | | | | | | | | MATERIAL: | | | |
| | | | | | | | | WEIGHT: | | | |